


FIG. 21 STEEL C-CLAMP
FIG. 21L STEEL C-CLAMP WITH LOCKNUT, DOMESTIC
FIG 21LI STEEL C-CLAMP WITH LOCKNUT



Material: Carbon steel, 304 stainless steel (21LSS) and 316 stainless steel (21LSX).

Finish: Plain, electro-galvanized.

Service: Designed for attaching hanger rod to the bottom flange of a beam. Features the ribbed design for added strength. Hardened steel cup point set screw secures clamp to beam.

Approvals: UL - U.L.C. listed and FM approved ($\frac{3}{8}$, $\frac{1}{2}$ with locknut only). Complies with Federal Specification WW-H-171-E (Type# 23), A-A-1192 A (Type# 23), Manufacturers' Standard Society SP-58 and MSS SP-69 (Type# 23)

Ordering: Specify rod size, figure number and finish.

Notes: See MSS SP-69 for proper set screw torque recommendations.

| SIZE A | SET SCREW | C | D | E | F | MAX PIPE SIZE | WGT EACH (lbs) | | MAX REC LOAD (lbs) |
|-------------------|-------------------|-----------------|------------------|-----------------|---------------|---------------------|----------------|-------------|-----------------------|
| | | | | | | | 21 (W/OUT NUT) | 21L (W/NUT) | |
| $\frac{3}{8}$ -16 | $\frac{3}{8}$ -16 | 2 $\frac{3}{8}$ | 2 $\frac{3}{8}$ | 1 | $\frac{3}{4}$ | 4 | .38 | .40 | 400 |
| $\frac{1}{2}$ -13 | $\frac{3}{8}$ -16 | 2 $\frac{3}{8}$ | 2 $\frac{3}{8}$ | 1 | $\frac{3}{4}$ | 4 | .38 | .40 | 500 |
| $\frac{5}{8}$ -11 | $\frac{1}{2}$ -13 | 2 $\frac{3}{8}$ | 2 $\frac{5}{16}$ | $\frac{7}{8}$ | $\frac{3}{4}$ | 5 | .56 | .60 | 550 |
| $\frac{3}{4}$ -10 | $\frac{5}{8}$ -11 | 2 $\frac{3}{8}$ | 2 $\frac{5}{16}$ | $\frac{7}{8}$ | $\frac{3}{4}$ | 6 | .60 | .68 | 630 |
| $\frac{7}{8}$ -9 | $\frac{3}{4}$ -10 | 3 | 3 $\frac{5}{16}$ | 1 $\frac{1}{4}$ | 1 | 8 | 1.76 | 1.88 | 1200 |

