


FIG. 23L
MALLEABLE IRON C-CLAMP WITH LOCKNUT



- Material:** Malleable iron.
- Finish:** Plain, electro-galvanized.
- Service:** Designed for attaching hanger rod to the bottom flange of a beam.
- Approvals:** U.L. - U.L.C. listed ($\frac{3}{8}$, $\frac{1}{2}$ with locknut only) and FM approved. Complies with Federal Specification WW-H-171-E (Type# 23), A-A-1192 A (Type# 23) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 23).
- Ordering:** Specify rod size, figure number and finish.
- Notes:** See MSS SP-69 for proper set screw torque recommendations.

SIZE A	SET SCREW	C	D	E	F	MAX PIPE SIZE	WGT EACH (lbs)	MAX REC LOAD (lbs)
$\frac{3}{8}$ -16	$\frac{3}{8}$ -16	1 $\frac{3}{4}$	1 $\frac{3}{4}$	$\frac{5}{8}$	$\frac{3}{4}$	4	0.40	400
$\frac{1}{2}$ -13	$\frac{3}{8}$ -16	1 $\frac{3}{4}$	1 $\frac{3}{4}$	$\frac{5}{8}$	$\frac{3}{4}$	4	0.39	500
$\frac{5}{8}$ -11	$\frac{3}{8}$ -16	2	2	$\frac{5}{8}$	$\frac{3}{4}$	5	0.65	550
$\frac{3}{4}$ -10	$\frac{3}{8}$ -16	2	2	$\frac{5}{8}$	$\frac{3}{4}$	6	0.76	630

